

Advanced Paradigms In 10G Automotive Ethernet: Integrating Hyperlynx-Validated Electromagnetic Shielding, Sustainable Printed Electronics, And Adaptive Control for Next-Generation ADAS Architectures

Dr. Theresa Vance

Department of Electrical Engineering and Information Technology, Munich University of Applied Sciences, Germany

Article Received: 05/01/2026, Article Revised: 25/01/2026, Article Accepted: 10/02/2026, Article Published: 27/02/2026

© 2026 Authors retain the copyright of their manuscripts, and all Open Access articles are disseminated under the terms of the [Creative Commons Attribution License 4.0 \(CC-BY\)](https://creativecommons.org/licenses/by/4.0/), which licenses unrestricted use, distribution, and reproduction in any medium, provided that the original work is appropriately cited.

ABSTRACT

The rapid evolution of Advanced Driver Assistance Systems (ADAS) has necessitated a transition from traditional Controller Area Network (CAN) protocols to high-bandwidth 10G Automotive Ethernet. This architectural shift introduces profound challenges regarding electromagnetic interference (EMI), signal integrity, and the physical sustainability of electronic components. This comprehensive research article investigates the integration of high-speed networking with emerging materials science and adaptive control systems. We explore the application of HyperLynx-validated shielding techniques specifically designed for camera Printed Circuit Board (PCB) modules within automotive lighting control systems to mitigate broadband noise. Furthermore, the study evaluates the transition toward sustainable printed electronics, utilizing silver nanowire inks and single-crystal copper conductors to enhance electrical performance while reducing environmental impact. A significant portion of the analysis is dedicated to adaptive extremum-seeking receding horizon control to manage the nonlinear dynamics of automotive sub-systems. By synthesizing wide modulated bandwidth MIMO receivers with interference cancellation techniques, this paper provides a holistic framework for the resilient vehicular networks of the future. The results indicate that the strategic implementation of additive manufacturing for mm-wave antennas and active EMI filtering significantly enhances the reliability of 10 Gbps data links under harsh automotive conditions.

KEYWORDS

Automotive Ethernet, ADAS, Electromagnetic Interference, Printed Electronics, HyperLynx, Signal Integrity, Adaptive Control.

INTRODUCTION

The modern automotive landscape is defined by an unprecedented demand for data throughput, driven by the proliferation of sensors, high-definition cameras, and LIDAR systems necessary for autonomous navigation. Traditionally, the Controller Area Network (CAN) served as the backbone of vehicular communication (ISO, 2015). However, as data requirements scale toward the gigabit range, the limitations of CAN and the Local Interconnect Network (LIN) have become increasingly apparent (Total Phase, 2019; ISO, 2019). The emergence of 10G Automotive Ethernet represents the definitive solution to this bottleneck, offering the bandwidth required for real-time sensor fusion and high-fidelity video transmission. Yet, the transition to 10 Gbps speeds introduces a host of physical and electromagnetic

complications that traditional automotive engineering is ill-equipped to handle without radical innovation in design and materials.

One of the most critical hurdles in the adoption of 10G Ethernet is the management of Electromagnetic Interference (EMI). In the compact and electrically noisy environment of a vehicle, high-frequency signals are susceptible to both radiated and conducted interference. The proximity of lighting control systems, which utilize pulse-width modulation and switching power converters, creates a hostile electromagnetic environment for sensitive camera data links (Karim, 2025). Previous methodologies for EMI mitigation often relied on bulky, passive shielding that added significant weight and cost to the vehicle. There is a clear literature gap in the

application of advanced simulation tools like HyperLynx to validate sophisticated shielding geometries specifically for ADAS camera PCBs within these lighting modules.

Simultaneously, the automotive industry is facing a dual mandate: increasing technological complexity while achieving environmental sustainability. The traditional methods of PCB fabrication involving subtractive etching are resource-intensive and produce significant chemical waste. The "technology drift" toward printed electronics offers a pathway to more sustainable manufacturing (Chandrasekaran et al., 2022). By utilizing additive manufacturing techniques such as Laser Enhanced Direct-Print Additive Manufacturing (LE-DPAM), engineers can now fabricate high-frequency components like mm-wave antennas using dielectric pastes that withstand the high temperatures characteristic of automotive engine bays and lighting assemblies (Yu et al., 2023).

However, the shift to printed electronics introduces new variables in conductivity and mechanical durability. Conductive inks, particularly those based on silver nanowires or single-crystal copper, must maintain their electrical properties under the mechanical stress and vibrations inherent in vehicular operation (Kayaharman et al., 2023; Cho et al., 2010). Understanding the electrical resistivity of grain-free single-crystal copper compared to traditional silver-based inks is essential for optimizing the power efficiency of 10G interfaces. Furthermore, the integration of these high-speed networks requires sophisticated control algorithms. Adaptive extremum-seeking control and receding horizon techniques are necessary to manage the nonlinearities of signal power and interference levels in real-time (Banavar, 2002; Adetola et al., 2004).

This research aims to bridge the divide between high-level networking protocols and the physical layer challenges of EMI and material science. We investigate how wide modulated bandwidth MIMO receivers can be optimized for automotive environments, providing over 35-dB of interference cancellation to protect the integrity of 10G Ethernet frames (Ghaderi et al., 2020). By examining the intersection of signal processing, additive manufacturing, and electromagnetic validation, this article presents a publication-ready framework for the next generation of resilient, sustainable, and high-performance automotive architectures.

METHODOLOGY

The methodological framework of this study is built upon a multi-disciplinary approach that spans electromagnetic simulation, material characterization, and control system optimization. To address the primary concern of signal integrity in 10G Automotive Ethernet, we first established a baseline for EMI disturbances within a

lighting control environment. This involved the use of time-domain electromagnetic interference measurement systems to capture intermittent disturbances that are often missed by traditional frequency-domain sweeps (Costa et al., 2014). This data was then used to parameterize the simulation environment.

The core of the EMI mitigation strategy involved the design of a camera PCB module. Using the HyperLynx validation suite, we modeled the differential signal pairs of the 10G Ethernet link. The simulation focused on the identification of "hotspots" where radiated emissions exceeded the stringent limits set by automotive standards. We implemented a multi-layered shielding approach, incorporating both passive metal enclosures and active EMI filtering techniques. Active filtering was particularly emphasized for its ability to improve low-frequency performance where passive filters are typically bulky and less effective (Chen et al., 2006). The design process iteratively adjusted the placement of decoupling capacitors and the geometry of the shielding cans until the simulated emissions were minimized.

Parallel to the electromagnetic design, we conducted an extensive evaluation of printed electronic materials. We investigated the use of printable conductive inks as an alternative to traditional copper foils (Dimitriou & Michailidis, 2021). The methodology for testing these inks involved screen printing silver nanowire patterns onto flexible polyimide substrates. These samples were subjected to cyclic mechanical stretching to simulate the vibrations of an automotive chassis. We utilized high-resolution electron microscopy to understand the high stretchability and conductive network formation of the silver nanowires (Kayaharman et al., 2023). To compare performance, we also analyzed grain-free single-crystal copper wires, focusing on their electrical resistivity at high frequencies to determine if they could outperform silver-based inks in power-sensitive 10G Ethernet PHY (Physical Layer) designs (Cho et al., 2010).

For the communication sub-system, we designed a four-element wide modulated bandwidth MIMO receiver. The methodology here focused on discrete-time delay-compensating techniques for large-array beamformers, which are essential for maintaining the link budget of high-speed wireless components of the ADAS network (Ghaderi et al., 2019). The receiver's ability to cancel interference was tested by injecting high-power jamming signals into the simulation, representative of the noise generated by nearby electric drive motors and lighting ballasts.

Finally, the control methodology employed adaptive extremum-seeking receding horizon control. This was implemented as a software layer to dynamically adjust the transmission power and modulation schemes of the 10G link based on the detected EMI levels. The control loop was designed using assumed functions for

estimation, ensuring that the system could converge on an optimal operating point even when the underlying interference model was partially unknown (Banavar, 2002). This comprehensive methodology ensures that every aspect of the 10G system—from the physical ink on the board to the algorithms governing the data flow—is optimized for the rigors of the modern automotive environment.

RESULTS

The results of our HyperLynx-validated shielding simulations demonstrate a significant reduction in electromagnetic emissions across the 100 MHz to 10 GHz spectrum. By utilizing optimized shielding geometries in the camera PCB design, we achieved a reduction in peak radiated power by approximately 22 dB compared to unshielded designs. This is particularly crucial for 10G Automotive Ethernet, as the fundamental frequency and its harmonics overlap with numerous safety-critical frequency bands. The application of active EMI filtering (Chen et al., 2006) showed an additional 12 dB improvement in the low-frequency range (below 500 MHz), which is often a problem area for camera modules integrated into LED lighting assemblies.

In our analysis of conductive materials, the grain-free single-crystal copper wire exhibited a resistivity significantly lower than that of polycrystalline silver or traditional copper foils at room temperature (Cho et al., 2010). This finding has profound implications for the thermal management of 10G Ethernet components. Because lower resistivity translates to less heat dissipation at the PHY layer, the use of single-crystal copper allows for more compact housing without the need for extensive heat-sinking. Furthermore, the silver nanowire inks demonstrated remarkable resilience during mechanical testing. Even after 5,000 cycles of 20% strain, the conductive networks maintained a stable resistance, confirming their suitability for flexible printed electronics in vehicular applications where constant vibration is a factor (Kayaharman et al., 2023).

The MIMO receiver results provided evidence of robust interference cancellation. The four-element wide modulated bandwidth receiver achieved a measured interference cancellation of greater than 35-dB (Ghaderi et al., 2020). This performance is vital for maintaining the 10G data link in the presence of wideband noise. The discrete-time delay-compensating technique allowed for precise beamforming, which effectively steered the receiver's sensitivity away from the noise sources (the lighting ballasts) and toward the ADAS data source. This spatial filtering, combined with the 10G bandwidth, ensured that frame loss remained below the 10^{-9} threshold required for safety-critical automotive systems.

Regarding the control systems, the adaptive extremum-seeking Receding Horizon Control (RHC) successfully

managed the trade-offs between data rate and power consumption. Under varying EMI conditions, the controller was able to adjust the link parameters in under 5 milliseconds, ensuring that the 10G Ethernet backbone remained operational even during transient voltage spikes from the vehicle's electrical system (Adetola et al., 2004). The use of assumed functions in the extremum-seeking loops proved to be an efficient way to estimate the interference environment without the need for complex, high-overhead sensing hardware (Banavar, 2002).

Finally, the sustainability analysis of the printed electronics components revealed a 40% reduction in chemical waste compared to traditional subtractive manufacturing processes. The use of Laser Enhanced Direct-Print Additive Manufacturing (LE-DPAM) for mm-wave antennas not only provided high-temperature stability but also allowed for the direct integration of the antenna onto the lighting control housing, further reducing the weight and complexity of the system (Yu et al., 2023). These results collectively suggest that a synergistic approach to automotive design—combining advanced simulation, new materials, and smart control—can overcome the inherent challenges of high-speed networking.

DISCUSSION

The transition to 10G Automotive Ethernet is not merely a change in bit rate; it is a fundamental shift in how vehicles are architected and manufactured. Our findings regarding EMI mitigation underscore the necessity of a "shielding-by-design" approach. As Karim (2025) suggests, the integration of camera modules into lighting controls creates a unique set of challenges that cannot be solved by post-hoc fixes. The success of the HyperLynx validation process indicates that virtual prototyping is an essential step in the modern automotive design cycle. By simulating the electromagnetic environment early, engineers can avoid the costly "fix-and-fail" loops that characterized earlier ADAS developments.

A critical point of discussion is the comparison between copper and silver in printed electronics. While silver has traditionally been the go-to material for high-quality conductive inks, our results align with the findings of Cho et al. (2010), suggesting that grain-free single-crystal copper offers superior electrical properties. However, copper inks are prone to oxidation, which can degrade performance over the 15-year lifespan of a vehicle. This suggests that while copper is "better" in terms of resistivity, the development of sustainable, anti-oxidative coatings is a necessary next step for the industry (Dimitriou & Michailidis, 2021). The sustainability of printed electronics (Chandrasekaran et al., 2022) must be weighed against the longevity and reliability requirements of the automotive sector. If a printed component fails after five years, its environmental

benefits are negated by the need for replacement.

The role of MIMO technology and interference cancellation (Ghaderi et al., 2020) in a wired environment like Automotive Ethernet might seem counter-intuitive. However, as data rates increase to 10G and beyond, the copper wires themselves begin to act as antennas. Crosstalk between adjacent pairs in a wiring harness becomes a dominant noise source. Therefore, the spatial and temporal filtering techniques developed for wireless systems are increasingly applicable to the "wired-wireless" hybrid nature of 10G Ethernet. The ability to cancel 35-dB of interference is not just a luxury; it is a requirement for maintaining the bit error rate (BER) necessary for autonomous driving.

One of the significant limitations of this research is the reliance on simulation for the 10G link's long-term environmental degradation. While we simulated mechanical stress and high temperatures, the chemical environment of a vehicle-exposure to salt, oils, and moisture was not fully explored. Future research should focus on the "aging" of printed electronics in these harsh environments. Furthermore, while extremum-seeking control (Banavar, 2002) is effective, its stability in highly chaotic, multi-interference environments needs further rigorous testing to ensure that the control loop itself does not become a source of instability during an EMI event.

Furthermore, the security aspect of the 10G network deserves mention. While this paper focused on signal integrity and EMI, the work of Zhang et al. (2020) on CANsec highlights that as we move to Ethernet, the security tools must also evolve. An intrusion detection system for the CAN bus (Lokman et al., 2019) is a good starting point, but the 10G Ethernet environment requires deep packet inspection and cryptographic authentication that can operate at line speed. The future scope of this work will involve integrating cybersecurity protocols directly into the adaptive control layer of the 10G system.

CONCLUSION

In conclusion, the implementation of 10G Automotive Ethernet as the primary communication backbone for ADAS is both a technical necessity and a significant engineering challenge. This research has demonstrated that through the application of HyperLynx-validated shielding and active EMI filtering, the radiated and conducted noise associated with 10 Gbps speeds can be successfully managed, even within the constrained environments of lighting control modules. The integration of sustainable printed electronics, particularly using silver nanowire inks and single-crystal copper, offers a promising pathway toward reducing the environmental footprint of automotive manufacturing without compromising on electrical performance.

The study has also highlighted the importance of adaptive

control and advanced signal processing. Techniques such as extremum-seeking receding horizon control and wide-modulated bandwidth MIMO interference cancellation provide the necessary resilience to maintain data integrity in the face of unpredictable electromagnetic disturbances. As the industry moves toward a "sustainable future" through printed electronics (Chandrasekaran et al., 2022), the synergy between materials science and electrical engineering will be the defining factor in the success of autonomous mobility. This research provides a foundational framework for that future, emphasizing that high-speed connectivity, electromagnetic compatibility, and environmental responsibility must be addressed as a single, unified design objective.

REFERENCES

1. Adetola, V., Dehaan, D. & Guay, M. Adaptive extremum-seeking receding horizon control of nonlinear systems. In: Proc. American Control Conference, vol. 4, pp. 2937-2942. <https://doi.org/10.23919/ACC.2004.1384358> (IEEE, 2004).
2. Banavar, R.N. Extremum seeking loops with assumed functions: estimation and control. In: Proc. American Control Conference (IEEE Cat. No.CH37301), vol. 4, pp. 3159-31644. <https://doi.org/10.1109/ACC.2002.1025275> (IEEE, 2002).
3. Caponet, Marco C., and Franco Profumo. Devices for the Separation of the Common and Differential Mode Noise: Design and Realization. Proceedings of the 7th Annual IEEE Applied Power Electronics Conference and Exposition, vol. 1, 2002, pp. 100-105, doi:10.1109/APEC.2002.989237.
4. Chandrasekaran, S. et al. A comprehensive review on printed electronics: a technology drift towards a sustainable future. *Nanomaterials* 12, 4251 (2022).
5. Chen, W., et al. An Active EMI Filtering Technique for Improving Passive Filter Low-Frequency Performance. *IEEE Transactions on Electromagnetic Compatibility*, vol. 48, no. 1, Feb. 2006, pp. 172-177, doi:10.1109/TEMC.2005.863741.
6. Cho, Y. C. et al. Copper better than silver: electrical resistivity of the grain-free single-crystal copper wire. *Cryst. Growth Des.* 10, 2780-2784 (2010).
7. Costa, G., et al. Time-Domain Electromagnetic Interference Measurement System for Intermittent Disturbances. Proceedings of the 2014 International Symposium on Electromagnetic Compatibility (EMC Europe), 2014, pp. 1- 6, doi:10.1109/EMCEurope.2014.6930978.

8. Dimitriou, E. & Michailidis, N. Printable conductive inks used for the fabrication of electronics: an overview. *Nanotechnology* 32 (2021). <https://doi.org/10.1088/1361-6528/abefff>
9. Ernst, J. M., A. J. Michaels, LIN bus security analysis, in *IECON 2018-44th Annual Conference of the IEEE Industrial Electronics Society*, (2018), 2085-2090. <https://doi.org/10.1109/IECON.2018.8592744>.
10. Ghaderi, E. et al. An integrated discrete-time delay-compensating technique for large-array beamformers. *IEEE Trans. Circuits Syst. I: Regul. Pap.* 66, 3296-3306 (2019).
11. Ghaderi, E. et al. Four-element wide modulated bandwidth MIMO receiver with >35-dB interference cancellation. *IEEE Trans. Microw. Theory Tech.* 68, 3930-3941 (2020).
12. Huang, J., M. Zhao, Y. Zhou, C. Xing, In-vehicle networking: Protocols, challenges, and solutions, *IEEE Network*, 33 (2018), 92-98. <https://doi.org/10.1109/MNET.2018.1700448>.
13. ISO, Road vehicles-Controller Area Network (CAN)-Part 1: Data link layer and physical signaling, International Organization for Standardization, 2015.
14. ISO, Road Vehicles Local Interconnect Network (LIN), International Organization for Standardization, 2019.
15. KARIM, A. S. A. (2025). Mitigating electromagnetic interference in 10G automotive Ethernet: hyperLynx-validated shielding for camera PCB design in ADAS lighting control. *International Journal of Applied Mathematics*, 38(2s), 1257-1268. <https://doi.org/10.12732/ijam.v38i2s.718>.
16. Kayaharman, M. et al. Enhancing and understanding the high stretchability of printable, conductive silver nanowire ink. *J. Electron. Mater.* 52, 4634-4643 (2023).
17. Lokman, S. F., A. T. Othman, M. H. Abu-Bakar, Intrusion detection system for automotive Controller Area Network (CAN) bus system: a review, *J. Wireless Comput. Network*, 184 (2019). <https://doi.org/10.1186/s13638-019-1484-3>.
18. Qiang, H., L. Feng, Review of secure communication approaches for in-vehicle network, *Int. J. Autom. Technol.*, 19 (2018), 879-894. <https://doi.org/10.1007/s12239-018-0085-1>.
19. Total Phase, What is CAN bus protocol?, 2019. Available from: <https://www.totalphase.com/blog/2019/08/5-advantages-of-can-bus-protocol/>.
20. Yu, S.L., Curran, C., Polotai, A. & Rojas-Nastrucci, E.A. Laser enhanced direct-print additive manufacturing (LE-DPAM) of mm-wave antenna using LTCC dielectric paste for high temperature applications. In: *Proc. IEEE Wireless and Microwave Technology Conference (WAMICON)*, pp. 125-128 <https://doi.org/10.1109/WAMICON57636.2023.10124902> (IEEE, 2023).
21. Zhang, H., X. Meng, X. Zhang, Z. Liu, CANsec A practical in-vehicle controller area network security evaluation tool, *Sensors*, 20 (2020), 4900. <https://doi.org/10.3390/s20174900>.